# **GETTING STARTED**

**BOOST** - To set up the Level Boost, plug your instrument into the Input Jack (5), and connect the Output Jack (6) to your amplifier, after connecting a +9/+12VDC power supply to the DC IN to the DC IN (7). Turn the boost on using the footswitch (3), making sure the LED (4) is ON (this indicates that the effect is active). Next, adjust the Boost Level slider while toggling the footswitch (3) on and off, comparing the volume of the direct signal with the boosted signal. Match the gain level as closely as you can to the direct signal, then adjust the Level Boost slider to the desired amount of added boost or cut. A suggested use of the boost is to leave it turned off until it's time to solo, then switch it on (3) for a guick level boost when you begin your solo. You can easily apply this to ANY situation where you need two different, quickly accessible playing volumes.

VPF (Variable Pre-shape Filter) - This filter boosts lows and highs, and cuts mids. Some call this kind of effect a scoop, a smiley-shape EQ, or an enhance knob. It's very effective for slap bass, pick playing, and driving eighth-note rock. It's off when it is all the way counterclockwise—we suggest you start in that position and turn the filter up gradually, to hear and understand what it does.

#### **TECHNICAL SPECS**

**INPUT IMPEDANCE:** 1 Mohm / 6 Vpp **OUTPUT IMPEDANCE:** 470 ohm / 6 Vpp

**BOOST:** 0 to +20dB (maximum gain)

POWER REQUIREMENTS- DC INPUT: +9/+12VDC

**DIMENSIONS:** 48.4 x 38.2 x 104.2 mm 1.91" x 1.5" x 4.1"

**WEIGHT:** 174 g


0.38 lbs

**BLOCK DIAGRAM** 

reserves the right to be the sole arbiter regarding the misuse or abuse of this product.

purchase in order to receive warranty service.

details.



vary from country to country; please contact the Markbass distributor in your country for However, please note that you are required to retain a copy of your receipt as proof of This warranty does not apply to any damage to the product caused by misuse, mishandling, Markbass assumes no liability for any incidental or consequential damages, which may result from the failure of this product. Any warranties implied in fact or by law are limited to the duration of this express limited warranty. Your legal rights related to the warranty will vary Markbass offers an international limited warranty on Markbass products purchased from any authorized Markbass dealer, effective from the day of purchase. The terms of this warranty Please register this product online at www.markbass.it to establish the date of purchase. accident, abuse, alteration, modification or unauthorized repairs. Product appearance and normal wear and tear (worn paint, scratches, etc.) are not covered by this warranty. Markbass

**OWNER'S MANUAL** 

A - The Markbass warranty is only applicable if this document been properly completed (here

or online) and if the original invoice/bill of sale, mentioning model, serial number and

purchase date, is presented together with this document

B - The obligations of Markbass are limited to the repair of defects. Warranty repair eligibility

This product is guaranteed by the warranty provided in the country of purchase, under the

following conditions:

depending on the country of purchase.

**WARRANTY CARD** 

an authorized Markbass (PARSEK) if the damage was caused by accident, negligence or modifications; use of non Markbass insurance costs, and any other costs related to the repair of this product are not covered by will be decided at the sole discretion of Markbass or its representatives. Freight, freight D - This warranty does not apply in the following instances: C - All warranty repairs must be made by Markbass or

service center.

this warranty.

· if the damage was caused by lightning, water, fire, incorrect main voltage, insufficient rentilation or any other cause beyond the control of Markbass. spare parts; or improper use, installation or packing; if the serial number on the equipment is illegible;

E - Markbass reserves the right to redesign or improve/modify its product at any time without any obligation to modify previously manufactured products.

Mini Boos

Parsek srl. - Italy - 66020 San Giovanni Teatino (Ch) - Via Po, 52/A Tel. +39 085 446 37 55 - Fax +39 085 440 77 64 - www.markbass.it - info@markbass.it

LIMITED WARRANTY

2) Keep these instructions:

3) Heed all warnings:



- 5) Do not use this apparatus near water:
- 6) Clean only with dry cloth
- Install in accordance with the manufacturer's instructions:
- 8) Do not install near any heat sources such as radiators, heat registers, stoyes, or other apparatuses (including amplifiers) that produce heat:

The Lightning Flash with arrowhead symbol

within an equilateral triangle, is intended to

alert the user to the presence of uninsulated

"dangerous voltage" within the product

enclosure that may be of sufficient magnitude

"The exclamation point within an equilateral

to the presence of important operating and

in the literature accompanying the product."

triangle is intended to alert the user

maintenance (servicing) instructions

to constitute a risk of shock to persons."

- 9) Protect the power cord from being walked on or pinched, particularly at plugs, convenience receptacles, and the point where they exit from the apparatus:
- 10) Only use attachments/accessories specified by the manufacturer:
- 11) Unplug this apparatus during lightning storms or when unused for long periods of time;
- 12) Refer all servicing to qualified service personnel. Servicing is required when the apparatus has been damaged in any way, such as when the power-supply cord or plug is damaged, liquid has been spilled or objects have fallen
- into the apparatus, or when the apparatus has been exposed to rain or moisture, does not operate normally, or has been 13) "Warning: to reduce the risk of fire or electric shock, do not expose this apparatus to rain or moisture; and objects filled with
- liquids, such as vases, should not be placed on this apparatus"
- 14) The socket outlet shall be installed near the equipment and shall be easily accessible:
- 15) The power cord must be unplugged prior to servicing.

### 1 PRÉCAUTIONS D'EMPLOI

- 1) Lire ces instructions:
- Conserver ces instructions:
- 3) Suivre tous les conseils d'utilisations:
- 4) Suivre toutes les instructions
- 5) Ne pas utiliser cet appareil au bord de l'eau; Nettover uniquement avec un chiffon humide
- 7) Ne pas bloquer le système de ventilation. Installer conformément aux instructions du fabricant:
- 8) Ne pas installer l'appareil près d'une source de chaleur tel qu'un radiateur, un fourneau, ou bien un autre appareil qui produit
- de la chaleur 9) Protéger le cordon d'alimentation afin qu'il ne soit pas piétiné ou écrasé tout particulièrement au niveau des fiches, des prises
- de courant femelles, et des parties qui sortent de l'appareil 10) Utiliser uniquement les accessoires recommendés par le fabricant;
- 11) Ne pas branché l'appareil en cas d'orage accompagné d'éclairs. Le débrancher en cas de non utilisation prolongée;
- 12) S'adresser à un service assistance agréé si l'appareil a subi des dommages, si le cordon d'alimentation ou la fiche a été endommagé, si un liquide a été renversé sur l'appareil ou bien si un object est tombé dans l'appareil, si ce dernier a été exposé à la pluie ou à l'humidité, s'il ne fonctionne pas correctement ou s'il est tombé,
- 13) "Avertissant: pour réduire le risque du feu ou de décharge électrique, n'exposez pas cet appareil à la pluie ou l'humidité et les
- objets remplis de liquides; tels que des vases, ne devraient pas être placés sur cet appareil" 14) La prise de courant doit être installée près de l'appareil et doit être facilement accessible;

- 15) La fiche principale doit être débranchée avant toute opération d'entretien
- MOR

For v www Conta

# **FUNCTIONS OVERVIEW**

**LEVEL BOOST (1) -** This control increases your instrument's volume without changing its sound (from 0dB to 20dB ), which is very useful for solos and any time you need to boost your signal without distortion.

**VPF FILTER CONTROL (2) -** The VPF (Variable Pre-shape Filter) boosts lows (around 35 Hz) and highs (around 10 kHz), and cuts mids at 380 Hz. This filter is especially great for rock music, slap bass and playing with a pick.

BOOST SWITCH\* (3) - The LED (4) indicates that the effect pedal is engaged.

# \*TRUE BYPASS

TRUE BYPASS - When the pedal's controls are 'off', your signal goes directly from the input jack to the output jack without any degradation of audio quality.

#### 5. CONNECTIONS

1/4" INPUT JACK (connects to your instrument) (5) - Make sure that your amp is off and the volume is turned down before making connections. Connect your instrument to the input of the MB Mini Boost and the output of the MB Mini Boost to your amplifier.

1/4" OUTPUT JACK (connects to your amplifier) (6)



urranty and service information, please contact your local Markbass distributor (contact information available at narkbass.it). For more technical information, please visit us at www.markbass.it and fill out the form on the t Us page. We hope you enjoy your effect pedal and use it to make great music!							DC IN (7) - External power supply connection: +9/+12VDC					
	□ Internet □ Retail Store  WHAT MOST INFLUENCED YOUR BUYING DECISION?	WHAT LEVEL OF PLAYER ARE YOU?  Beginner  Professional  PRODUCT PURCHASED VIA:	。 □ Stage / Performing Musician □ Classroom / Educator	MORE INFO (* not mandatory)  *Age *Occupation WHERE DO YOU PLAY YOUR INSTRUMENT?	Zip	Your Email Address	Purchased by: First Name	_	PRODUCT INFORMATION  Model  Date of Purchase	We'd like to thank you for choosing a Markbass product.  If any problem occurs, please don't hesitate to contact our support team at service@markbass.it.  You can fill out this form and send a copy to Markbass (Parsek srl, Via Po 52, 66020 San Giovanni Teatino, CHIETI ITALY) or, even better, you can now register your warranty online in a matter of minutes, using our online registration form at www.markbass.it. Simply point, click and type in your informationand you're done!  Registering your warranty identifies you and your product, in case you are ever in need of warranty service. Please note that in order to qualify for warranty service, you must retain a copy of the sales receipt or bill of delivery as proof of purchase.  The information that you provide here will not be shared with any third parties and will be used for Markbass internal business purposes only.		
	□ Retail Store	□ Amateur □	ool / Student me	*Sex*Sex	Country	Address State/Prov	Last Name		Dealer City	Serial Number(mm/dd/yyyy)	Markbass product. don't hesitate to contact or opy to Markbass (Parsek srl, Via Poyou can now register your warrar form at www.markbass.it. Simply you and your product, in case y order to qualify for warranty ser very as proof of purchase.  e will not be shared with any third ses only.	
		□ Semi-Professional	□ Studio Recording								our support team at Po 52, 66020 San Giovanni ranty online in a matter of ply point, click and type in you are ever in need of service, you must retain a rd parties and will be used	

WARRANTY CARD